



Food2Go

Active Cooling + Hot

Food2Go is a mobile serving platform for cook to serve applications. A perfect product when you need a versatile all-in-one product for transporting, holding and serving meals. The unit transports plates, single-portions, as well as containers. The spacious top surface fits up to three full size GN 1/1 containers with two GN 1/1 built-in ceramic heating plates to assure maintained temperatures during food service. Other features are adjustable ventilation for optimal moisture control, ergonomic push/pull handles and big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Compressor cooling is standard and convection heating is offered as an option.

Outer Measurement

| | |
|---------------|---------|
| Width | 780 mm |
| Height | 1357 mm |
| Depth | 1320 mm |

Inner Measurement

| | |
|---------------------------|--------------|
| Width | 330 mm |
| Height | 576 mm |
| Depth (cold / hot) | 596 / 553 mm |

Capacity & Weight

| | |
|--|---|
| Capacity | 7 + 7 x 1/1GN with 80 mm distance between runners |
| Maximum Loading Capacity / Runner | 9 kg |
| Net Weight | 140 kg |
| Volume | 113 L Cold Chamber / 105 L Hot Chamber |

Features

| | |
|------------------|---|
| Color | Black (RAL 9005) is standard. Red (RAL 3003) and Grey (RAL 7042). Free of charge. |
| Signature | Put your logo on the box or wrap it in your pattern. |

Construction & Electrics

| | |
|-------------------------|--|
| Interior | Anodized aluminium |
| Rack | Detachable laser cut U-shaped runners in SST |
| Exterior | Fiber glass plastic and aluminum profiles |
| Door Handle | One Grip Handle is standard |
| Door Opening | – |
| Chassi | Stainless Steel with rubber clad |
| Power Connection | 220V-240V / 1 phase / 50-60Hz |

Active Cooling

| | |
|---------------------------|---------------|
| Compressor Cooling | Yes |
| Consumption W/A | See below |
| Temperature Range | +3°C to +10°C |
| DB / ΔT / IP Class | 63 / 30° / 21 |

Totat W/A incl. hot plate 864W / 4,23A

Hot

| | |
|--------------------------|------------|
| Heating Element | Yes |
| Consumption W/A | See below |
| Temperature Range | Up to 90°C |

Functions, Safety & Ergonomics

| | |
|-------------------------------|--|
| Digital Display | Yes, with temperature reached indicator |
| Adjustable Ventilation | Yes, open & close to adjust moisture level |
| Tray Stop | Protects from door scratches & trays moving |
| Runner Tilt Stop | Extra safety when loading/unloading the box |
| Classifications | CE, EMC, RoHS, REACH |
| Castors (standard) | Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake) |
| Handles | Ergonomic push/pull handles |
| Extra Loading Spaces | – |

Options

| | | |
|-----------------------------|--------------------------------|--------------------------|
| Tray Holder | Card Holders A4/A5/A6 | Stainless Steel Interior |
| Tray Slide | Ergo Drive+ Motorized Chassi | |
| Condiment Holder | Ø 200mm Castors | |
| Dustbin Holder | Tow Bars | |
| Countertop Slots | Customized Spacing for Runners | |
| One Grip Handle w. Lock Key | Pressed Runners | |

For detailed information of available options please refer to scanbox.se